

FUNMAT PRO 410

A Multiple Functional Materials All-in-one Solution Designed and Manufactured by INTAMSYS
Ideal for Industrial Additive Manufacturing



FUNctional MATerials



Advanced
Thermal Design



Dual Nozzle 3D
Printing Solutions



High Speed,
High Precision



AUTO Sensor Assisted
Automatic Leveling



Smart Design for
Continuous Production



Multiple Functional
Materials



High Safety
Standards



Comfortable &
Easy-to-use Interface

PEEK, PEEK-CF, PEKK, PEI, PPSU, PA, PA-CF, PC, ABS ...

Technical Specifications

SIZE & WEIGHT

Printer Size	720 × 670 × 1460 mm
Printer Weight	200 kg

PRINTING

Printing Technology	FFF (Fused Filament Fabrication)
Build Volume	305 × 305 × 406 mm (12 × 12 × 16 inches)
Layer Thickness	50 μm, 0.1 mm, 0.15 mm, 0.2 mm, 0.3 mm
Printing Nozzles	2 Printing Nozzles Without Scratching
Printing Speed	300 mm/s
Nozzle Diameter	0.25 mm, 0.4 mm, 0.5 mm, 0.6 mm, 0.8 mm, 1.2 mm
Nozzle Cleaning	Auto-cleaning station
Filament Diameter	1.75 mm
Filament Type	PEEK, PEKK, PEI, PPSU, PC, Nylon, ABS, PLA, PVA, TPU, Carbonfiber Reinforcement, etc..
Camera	Yes
Leveling	Auto-leveling with High Precision Sensors
Extruder Temperature	450°C
Platform Temperature	160°C
Chamber Temperature	90°C
Smart Monitor & Control	Jam Warning Filament, Filament Absence Warning, Power Failure Recovery

MECHANICAL

Build Plate	Glass Ceramics
Filament Chamber	Heated Dry Box
XY Resolution	0.016 mm
Z Resolution	0.0016 mm

ELECTRICAL

Input	220V/9A
Power Consumption	2000 W
Connectivity	WiFi, Internet, USB
Touch Screen	7 Inch Smart Touch Panel
Safety	EN60950
Regulatory Compliance	CE

SOFTWARE

Slicing Software	IntamSuit, Simplify 3D, Cura
Supported File Types	.stl, .obj
Host Platform	Windows

ENVIRONMENT

Operating Temperature	15–30°C
Storage Temperature	0–30°C

