LASER SYSTEMS ILS9.75

36" x 24" Work Area



Uniquely Universal Features

Laser Interface+™

Universal Laser Systems has developed the world's most advanced, powerful and flexible laser print driver.

1-Touch Laser Photo™

We developed this software to make any photographic image suitable for laser engraving.

Universal Laser Sources

Our exclusive line of patented CO2 Free-Space Gas Slab Lasers is designed specifically for the needs of laser cutting, engraving, graphic imaging and marking applications.

High Power Density Focusing Optics™

These optics allow the laser beam to be focused to a much smaller spot, producing sharper images at tighter tolerances.

Rapid Reconfiguration™

Every laser cartridge we produce is factory pre-aligned for easy integration into any of our laser platforms.

Dual Laser Configuration

Giving you the ability to merge two independent laser sources into a single beam for additional power and flexibility.

SuperSpeed™

This innovation pulses the two lasers independently, allowing for two lines of a raster image to be marked

Pass-Through Mode

Our versatile ILS platform is designed to accommodate laser processing of continuous materials, such as long sheet goods or rolled materials.

Platform Overview

The ILS9.75 platform is designed for laser material processing in a wide variety of production environments. Flexible enough to be installed as a standalone system or integrated into an automated manufacturing line, the ILS9.75 is an excellent choice for no-tool prototype production and is also used in research and development facilities around the world. In addition to a spacious 36" x 24" x 12", 10,368 in3 (914 x 610 x 305mm, 169,901 cm3) material processing envelope, the ILS9.75 incorporates our Pass-Through feature, which allows both side doors to be opened to process material of unlimited length. Universal's ILS platforms are also the only CO2 laser systems in the world that can be converted between CDRH Class 1 and CDRH Class 4.

The ILS9.75 is dual laser compatible and has a processing power range of 10 watts, when using our smallest laser cartridge, to 150 watts when using two of our 75-watt lasers. In addition to the basic capabilities of the machine, there are a number of patented Uniquely Universal features that are only available from Universal Laser Systems. These include Laser Interface+ and Rapid Reconfiguration; Dual Laser Configuration, Super Speed and Pass-Through are additional optional features that will reduce downtime and increase productivity. All Universal laser platforms use interchangeable components, giving you the ability to tailor your system to fit your needs.



LASER SYSTEMS ILS9.75 36" x 24" Work Area

System Specifications

Work Surface Area	36 x 24 in (914 x 610mm)
Maximum Part Size	40.5 x 30 x 12 in (1029 x 762 x 305mm)
Dimensions	57 x 44 x 46 in (1448 x 1105 x 1168 mm)
Rotary Capacity	Max Diameter 10.25 in (260 mm)
Motorized Z Axis Lifting Capacity	60 lbs (27 kg)
Pass-Through™ Class 4 Mode Work Area	24 x ∞ in (610 x ∞ mm)
Pass-Through™ Class 4 Mode Clearance	23.75 x 8 in (603 x 203 mm)
Available Focus Lenses CO2	1.5 in (38 mm)
	2.0 in (51 mm) *standard
	3.0 in (76 mm)
Laser Platform Interface Panel	Keypad and LCD display shows current file name,
	laser power, engraving speed, PPI and run time.
Operating System Compatibility	Requires a dedicated PC to operate.
	Compatible with Windows XP/Vista/7 32/64 bit
PC Connection	USB 2.0
Optics Protection	Plumbed for compressed-air-based optics protection.
Cabinet Style	Floor-Standing
Laser Options	10, 25, 30, 40, 50, 60 and 75 Watts
	Dual Laser Configuration optional
Approximate Weight	400 lbs (181 kg)
Power Requirements	220V-240V/10A (1 laser) 220-240V/16A (2 lasers)
Exhaust Connection	Two 4 in (102 mm) ports
	700 CFM @ 6 in static pressure (1700 m3/hr at 1.5 kPa)

System Features

Laminated Safety Glass Over-temp Alarm (for fire safety) Multiple Automatic Focusing Modes Precision Digital Motors LCD display Wraparound Top and Front Door Covered V-Groove Rail System Multiple Language Support Permanently Sealed Bearings Proportional Pulse Control Stretch-Free Kevlar[®] Belts

Laser Features

Laser Fan Control (to reduce noise) Smart Lasers Laser Pointer Wide Selection of Power Levels Air-Cooled Laser Cartridge Patented Permalign™ No Optical Beam Alignment Required Patented Cross-Platform Compatibility Patented Free-Space Gas Slab Laser Design High Reliability, Excellent Power Stability Warranty Available Up To 5 Years





